CIRCUIT RACING SLICKS - BIAS

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUND SOFT TO FIRM
43101	18.0 x 6.0-10 C2000	F500	6.2″	18.1″	57.0″	6″	6″	8.1″	R25B, R35B
43105	18.0 x 7.5-10	F500	7.5″	18.3″	57.5″	7-8″	8″	9.5″	R25B, R35B
43110	19.5 x 6.5-10	F500	6.5″	19.4″	61.0″	6″	6″	8.2″	R25B
43120	19.5 x 7.5-10	F500	7.5″	19.5″	61.2″	7-8″	8″	9.5″	R25B
43130	20.0 x 6.0-13	CF	6.0″	20.7″	65.0″	5.5-6.5″	5.5″	7.0″	R60A
43163	20.5 x 7.0-13 A2500	FB, FC, FM, SR	6.75″	20.8″	66.2″	6-8″	6″	8.0″	R25B, R35B
43168	20.0 x 7.5-13 A2500	SR	8.0″	20.6″	65.0″	6-9″	8″	9.4″	R25B, R35B
43172	20.0 x 8.0-13 C3500	FP, HP, GT3, GTL	8.0″	20.0″	63.0″	5-6″	6″	9.2″	R35B, R45B
43186	20.0 x 9.0-13 A2500	FA, SR	9.75″	20.6″	64.7″	8-10″	10″	11.0″	R25B, R35B
43192	20.0 x 9.5-13 C3500	EP, FP, GT3, GTL	9.4″	20.0″	63.0″	7″	7″	10.5″	R35B, R45B
43272	22.0 x 8.0-13	SCCA-FE, SR	8.5″	22.0″	69.3″	8″	8″	9.6″	FE
43286	22.0 x 8.0-13 A2000	FB, FC, FM, SR	8.5″	22.0″	69.0″	8-10″	8″	9.9″	R25B, R35B
43294	22.0 x 9.0-13 A2500	FA, FB, FC, FM, SR	8.8″	22.1″	69.5″	8-10″	8″	10.0″	R25B, R35B
43307	22.5 x 7.2-13	CF	7.25″	22.6″	71.0″	5.5″	5.5″	9.8″	R60A
43309	22.5 x 7.2-13 A2500	FF	7.25″	22.6″	71.0″	5.5″	5.5″	9.8″	R25B
43312	22.0 x 10.0-13	SCCA-FE, SR	10.3″	22.0″	71.5″	10″	10″	11.8″	FE
43314	22.5 x 10.0-13 A2500	SR	9.8″	22.6″	71.0″	8-10″	10″	11.0″	R25B, R35B
43319	23.0 x 12.0-13 A3000	FA, SR	12.0″	23.6″	74.1″	12-15″	15″	15.9″	R25B, R35B
43337	21.0 x 5.0-15 C4000	FV	5.0″	21.2″	66.5″	4″	4″	5.5″	FVS
43353	22.5 x 5.5-15 C4000	FV	5.5″	21.9″	69.0″	4″	4″	6.5″	FVS
43384	23.0 x 9.5-15 C3500	EP, FP, GT3, GTL	9.2″	22.8″	71.5″	6-7″	7″	9.4″	R35B, R45B

ALL TREAD PATTERNS SLICK

SOFT — F1600 — FIRM

R25B R35B R45B FVS R60A

CIRCUIT RACING SLICKS - RADIAL

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUND SOFT TO FIRM
43322	185/60R13	FF	6.4″	21.8″	68.7″	5.5″	5.5″	7.7″	R60A
43327	205/60R13	FF	8.0″	22.7″	71.4″	5.5″	5.5″	8.7″	R60A
43331	210/550R13	P1, Pro Mazda	8.7″	21.8″	68.5″	8-10″	10″	10.5″	R35B, R55A
43333	275/570R13	P1, Pro Mazda	10.75″	22.5″	70.7″	10-12″	12″	12.56″	R35B, R55A
43548	190/530R13	PROD., GT	7.3″	20.8″	65.3″	6-7″	6″	7.8″	S80
43549	215/530R13	PROD., GT	8.3″	20.8″	65.4″	6-7″	7″	8.8″	S75, S80
43553	200/580R15	RADICAL	8.0″	22.9″	71.9″	6.5-8″	8″	8.8″	R55A
43558	215/580R15	PROD., GT	8.6″	22.9″	71.8″	7-9″	7″	9.7″	S75, S80, S100
43568	245/580R15	PROD., GT	9.4″	22.9″	71.8″	7-10″	7″	10.0″	S75, S80, S100
43573	23.0 x 9.5R15	FA	9.4″	22.9″	72.0″	10″	10″	10.7″	IL
43588	24.5 x 13.75R15	FA	13.75″	24.5″	77.0″	14″	14″	14.5″	IL
43591	27.5 x 11.5R15	HSC	11.5″	27.4″	86.0″	10″	9.5″	12.8″	R75A
43656	23.5 x 11.0R16	GT2	10.6″	23.6″	74.0″	10″	10″	11.0″	R75A
43661	23.5 x 12.0R16	GT2	12.0″	23.5″	73.8″	12″	12″	13.0″	R75A
43663	265/605R16	RADICAL	9.7″	23.9″	75.1″	9-10″	10″	10.9″	R55A
43672	25.5 x 12.5R16 C2000	GT1	12.4″	25.8″	81.0″	12″	12″	13.5″	R75A
43674	25.5 x 14.0R16 C2500	GT1	13.6″	25.7″	80.9″	12″	12″	14.1″	R70A
43696	28.0 x 14.5R16 C2500	GT1	13.9″	28.2″	88.5″	13″	13″	15.1″	R70A
43710	200/610R17		7.7″	23.9″	75.0″	7-8″	7.5″	8.2″	S100, S120
43722	230/610R17		9.0″	23.9″	75.1″	9″	9″	9.75″	S100
43740	265/630R17		10.1″	24.8″	77.9″	9-10″	10″	10.7″	S100
43822	240/640R18		9.1″	25.6″	80.4″	8-9.5″	9″	9.8″	S100
43831	255/645R18		9.8″	25.5″	80.0″	10″	10″	10.9″	S100
43837	265/650R18		10.1″	25.5″	80.0″	9-10″	10″	10.9″	S100
43850	285/650R18		11.0″	25.5″	80.5″	10-12″	11″	11.9″	S80, S100
43851	280/680R18		10.0"	26.9"	84.6"	9-11"	10"	11.3"	S100
43865	305/650R18		11.8″	25.6″	80.6″	11-13″	12″	12.7″	S100
43871	320/650R18		12.0″	25.8″	80.8″	11-13″	12″	13.0″	S100
43891	310/710R18		12.5″	28.2″	88.4″	10-12″	12″	13.6″	S100
43896	355/650R18		13.8″	25.7″	80.8″	12-14″	13″	14.2″	S100

ALL TREAD PATTERNS ARE SLICKS

SOFT — IL — S75 R55A — S80 — S100.....S120 — FIRM

R25B R35B R70A

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.

REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

CIRCUIT RACING WETS - BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	APPLICATION
44115	18.0 x 6.0-10	FSAE Wet	6.2″	17.8″	56.0″	6-8″	6″	7.8″	F500, FSAE
44125	19.5 x 6.5-10	Circuit Wet	6.2″	19.7″	62.0″	6-8″	8″	8.2″	F500
44150	20.0 x 7.5-13	Circuit Wet	7.4″	20.6″	64.6″	7-8″	7″	8.3″	CSR, FA
44185	21.0 x 6.5-13	Circuit Wet	6.7″	21.2″	65.5″	6-8″	6″	7.2″	FF, FM, FC, S2000, DSR
44195	22.0 x 7.5-13 W3	Circuit Wet	7.8″	21.3″	67.0″	8.0″	8″	8.9″	SCCA-FE
44217	22.0 x 9.0-13 W3	Circuit Wet	9.6″	22.6″	71.0″	8.5-10″	9″	10.6″	SCCA-FE, FC, FA, FM, P1, P2
44266	22.5 x 5.0-15	Circuit Wet	5.0″	22.0″	69.2″	4.0″	4″	6.5″	FV
44298	25.5 x 8.5-15	Vintage Wet	8.1″	25.3″	79.8″	7-8″	8″	10.3″	Historic
44307	27.0 x 10.0-15	Vintage Wet	10.0″	27.0″	84.0″	10-11″	10″	12.5″	HSC/GTA

CIRCUIT RACING WETS - RADIALS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	APPLICATION
44421	185/60R13 WET	DOT Radial Wet	6.5″	21.7″	68.0″	5.5″	5.5″	7.5″	FF
44426	205/60R13 WET	DOT Radial Wet	7.4″	23.2″	72.5″	5.5″	5.5″	8.4″	FF
44442	20.5 x 7.0R13	Circuit Radial Wet	7.2″	20.8″	65.3″	6″	6″	7.8″	F2000
44443	22.5 x 8.0R13	Circuit Radial Wet	8.3″	22.4″	70.5″	8″	8″	9.8″	F2000
44511	23.0 x 9.0R-15	Circuit Radial Wet	9.4″	23.0″	72.3″	10″	10″	10.7″	FA
44516	24.5 x 13.0R-15	Circuit Radial Wet	13.0″	24.4″	76.6″	14″	14″	15.1″	FA
44670	25.5 x 12.0R-16	Circuit Radial Wet	12.2″	25.7″	80.9″	12″	12″	13.2″	GT1, GT2
44690	28.0 x 12.5R-16	Circuit Radial Wet	13.6″	27.3″	85.7″	12″	12″	14.2″	GT1

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.

REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

VINTAGE

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	MODEL
43195	20.0 x 10.0-13	Slick	10.0"	19.8"	62.4"	10"	10"	11.6"	F5000, R35B
43385	23.5 x 10.5-15	Slick	10.8"	23.4"	73.6"	11.5"	11.5"	13.0"	F5000, Can AM, R35B
43386	26.0 x 16.2-15	Slick.	15.4"	26.0"	81.4"	17"	17"	18.3"	F5000, Can AM, R35B
44391	19.5 x 5.0-10	T.D.R.	5.2"	18.8"	59.0"	5-6"	5.5"	7.8"	HOOSIER T.D. R
44355	20.5 x 6.0-13	T.D.R.	6.2"	20.6"	64.7"	5-7"	5.0"	7.0"	HOOSIER T.D. R
44356	20.5 x 8.0-13	T.D.R.	7.8"	20.8"	65.5"	6.5-8.5"	7.5"	9.0"	HOOSIER T.D. R
44365	22.5 x 6.0-13	T.D.R.	6.2"	22.4"	70.3"	5-7"	5.0"	7.5"	HOOSIER T.D. R
44415	23.0 x 6.5-14	T.D.R.	7.2"	23.0"	72.3"	6-8"	5.5"	8.3"	HOOSIER T.D. R
44416	23.0 x 7.5-14	T.D.R.	7.8"	23.0"	72.5"	7-9"	6.0"	8.8"	HOOSIER T.D. R
44561	23.0 x 6.5-15	T.D.R.	6.7"	23.0"	72.5"	5.5-7"	6.0"	7.6"	HOOSIER T.D. R
44562	23.0 x 7.5-15	T.D.R.	7.6"	23.0"	72.5"	6.5-8.5"	7.5"	8.5"	HOOSIER T.D. R
44563	24.0 x 7.0-15	T.D.R.	7.0"	24.0"	75.5"	6.5-8.5"	6.0"	8.5"	HOOSIER T.D. R
44564	24.0 x 8.5-15	T.D.R.	8.5"	24.0"	75.5"	7.5-9.5"	8.0"	10.0"	HOOSIER T.D. R
44566	25.5 x 8.0-15	T.D.R.	8.0"	24.8"	77.8"	7-9"	6.0"	9.2"	HOOSIER T.D. R
44287	25.5 x 8.5-15	T.D.R.	8.5"	25.2"	79.2"	8-10"	8.0"	10.3"	HOOSIER T.D. R
44297	25.5 x 10.0-15	T.D.R.	10.0"	25.8"	81.0"	8-11"	8.0"	11.2"	HOOSIER T.D. R
44567	26.5 x 8.0-15	T.D.R.	8.0"	26.4"	83.0"	9-9.5"	7.0"	10.0"	HOOSIER T.D. R
44308	26.5 x 9.5-15	T.D.R.	9.5"	26.6"	83.5"	8-10"	8.0"	11.0"	HOOSIER T.D. R
44309	26.5 x 11.0-15	T.D.R.	10.4"	27.0"	84.9"	9-11"	12.0"	13.6"	HOOSIER T.D. R
44317	27.5 x 11.0-15	T.D.R.	11.0"	27.7"	87.0"	10-13"	10.0"	13.2"	HOOSIER T.D. R
44337	24.0 x 8.5-16	T.D.R.	8.2"	24.1"	75.4"	8-10"	8.0"	10.5"	HOOSIER T.D. R
44347	25.5 x 10.0-16	T.D.R.	10.0"	25.6"	80.5"	9-11"	9.0"	11.3"	HOOSIER T.D. R
44165	135/545-13	Vintage	5.4"	21.3"	67.0"	5.5"	5.0"	6.6"	VFF
44170	165/580-13	Vintage	6.8"	22.7"	71.2"	5.5"	6.0"	8.5"	VFF
44380	22.0 x 7.0-13	Vintage	6.8"	20.9"	68.8"	5.5-7.5"	5.5"	7.8"	WET
44205	21.0 x 9.0-13	Vintage	9.125"	20.9"	65.6"	10.0"	10.0"	10.5"	Vintage, FB R35B
44225	23.0 x 12.0-13	Vintage	13.0"	23.3"	73.25"	13.0"	13.0"	14.375"	Vintage, FB R35B
44405	120/590-15	Vintage	4.8"	22.6"	70.9"	4.5"	4.5"	6.1"	VINTAGE T.D.
44408	135/620-15	Vintage	5.6"	24.1"	75.6"	4.5"	4.5"	6.9"	VINTAGE T.D.
44400	5.00-15	Vintage	5.2"	24.7"	77.6"	4-6"	4.0"	7.0"	VINTAGE T.D.
44410	5.50-15	Vintage	6.5"	24.7"	77.6"	4.5-7"	4.5"	7.7"	VINTAGE T.D.
46003	P205/60R13	Speedster	7.3"	22.7"	71.2"	6.0"	6.0"	8.4"	SPEEDSTER
46007	P205/55R14	Speedster	7.3"	22.8"	71.6"	6.5"	6.5"	8.5"	SPEEDSTER
46011	P185/65R15	Speedster	6.4"	24.2"	76.0"	5-6.5"	5.0"	7.0"	SPEEDSTER
46014	P205/50R15	Speedster	7.3"	22.7"	71.4"	7.0"	7.0"	8.3"	SPEEDSTER
46015	P205/60R15	Speedster	7.3"	24.2"	76.0"	5.5-7.5"	6.5"	8.2"	SPEEDSTER
46021	P225/50R15	Speedster	8.1"	24.2"	76.0"	6-8"	7.0"	9.125"	SPEEDSTER

WARNING: *DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for making and performance only and are* ***NOT INTENDED FOR HIGHWAY USE.*** *It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible* ***SERIOUS PERSONAL INJURY OR DEATH.***

CIRCUIT RACING D.O.T. - RADIAL

ITEM NUMBER	TIRE SIZE	LOAD/SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	A7	R7
46302	P185/60ZR13	80W	A7 / R7	6.9"	21.7"	68.2"	6.0-7.0"	6.0"	7.8"		X
46304	P205/60ZR13	86W	A7 / R7	8.0"	22.8"	71.7"	5.5-7.5"	6.0"	8.8"		X
46309	P225/45ZR13	77W	A7 / R7	8.5"	20.9"	65.8"	7.0-8.5"	7.5"	9.3"	X	X
46312	P225/50ZR13	88W	A7 / R7	8.5"	21.9"	69.0"	6.0-8.0"	7.0"	9.4"		X
46322	P255/40ZR13	82W	A7 / R7	9.5"	20.9"	65.6"	8.5-10.0"	9.0"	10.5"	X	
46406	P205/55ZR14	85W	A7 / R7	8.1"	22.8"	71.6"	5.5-7.5"	7.0"	9.1"		X
46416	P225/50ZR14	88W	A7 / R7	8.5"	22.9"	72.0"	6.0-8.0"	7.0"	9.4"		X
46502	P205/50ZR15	84W	A7 / R7	8.0"	22.8"	71.8"	5.5-7.5"	6.5"	8.5"	X	X
46501	P205/50ZR15 SM7	Racing D.O.T. Radial		8.0"	22.8"	71.7"	5.0-5.75"	6.5"	8.7"	X	
46511	P225/45ZR15	81W	A7 / R7	8.6"	22.8"	71.8"	7.0-8.5"	7.5"	9.3"	X	X
46516	P225/50ZR15	90W	A7 / R7	8.8"	23.8"	74.8"	6.0-8.0"	7.0"	9.7"		X
46522	P245/40ZR15	83W	A7 / R7	9.0"	23.0"	72.0"	8.0-9.5"	8.5"	10.0"	X	X

CIRCUIT RACING D.O.T. - RADIAL CONTINUED

ITEM NUMBER	TIRE SIZE	LOAD/SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	A7	R7
46526	P245/50ZR15	95W	A7 / R7	9.4″	24.4″	76.2″	7.0-8.5″	7.5″	10.3″		X
46536	P275/35ZR15	82W	A7 / R7	10.1″	23.0″	72.2″	9.0-11.0″	9.5″	10.8″	X	X
46540	P275/50ZR15	101W	A7 / R7	10.0″	25.5″	80.0″	7.5-9.5″	8.0″	10.8″		X
46560	P295/35ZR15	101W	A7 / R7	10.5″	23.0″	72.3″	9.0-11.0″	10.0″	11.6″	X	X
46601	P205/45ZR16	77W	A7 / R7	8.0″	23.0″	72.1″	7.0-8.5″	7.0"	8.5″	X	X
46611	P225/50ZR16	91W	A7 / R7	8.8″	24.7″	77.6″	6.0-8.0″	7.0″	9.4″	X	X
46616	P245/45ZR16	88W	A7 / R7	9.5″	24.4″	76.5″	7.5-9.0″	8.0″	10.3″	X	X
46620	P255/50ZR16	99W	A7 / R7	9.4″	26.2″	82.2″	7.0-9.0″	8.0″	10.5″		X
46630	P275/45ZR16	94W	A7 / R7	10.3″	25.6″	80.5″	8.5-10.0″	9.0″	11.2″	X	X
46706	P225/40ZR17	81W	A7 / R7	9.0″	23.8″	74.8″	8.0-9.5″	8.0″	9.6″	X	X
46711	P225/45ZR17	84W	A7 / R7	9.0″	24.7″	77.8″	8.0-9.5″	7.5″	9.7″	X	X
46716	P245/40ZR17	86W	A7 / R7	9.7″	24.3″	76.0″	8.0-9.5″	8.5″	10.3″	X	X
46721	P245/45ZR17	89W	A7 / R7	9.3″	25.5″	80.0″	7.5-9.0″	8.0″	10.0		X
46729	P275/35ZR17	85W	A7 / R7	10.3″	24.7″	77.7″	9.0-11.0″	9.5″	11.0″	X	X
46730	P275/40ZR17	93W	A7 / R7	10.3″	25.5″	80.1″	9.0-11.0″	9.5″	11.0″	X	X
46733	P295/35ZR17	89W	A7 / R7	10.8″	25.3″	79.5″	9.5-11.0″	10.0″	11.6″	X	X
46735	P315/35ZR17	93W	A7 / R7	11.8″	25.6″	80.4″	11.0-12.0″	11.0″	12.6″	X	X
46740	P335/35ZR17	97W	A7 / R7	12.9″	25.6″	80.5″	11.0-13.0″	12.0″	13.6″	X	
46811	P225/40ZR18	83W	A7 / R7	8.8″	24.7″	77.6″	7.5-9.0″	8.0″	9.6″		X
46821	P245/35ZR18	80W	A7 / R7	9.4″	24.4″	76.7″	8.0-9.5″	8.5″	9.9″	X	X
46826	P245/40ZR18	88W	A7 / R7	9.0″	25.4″	79.8″	8.0-9.5″	8.5″	10.3″	X	X
46832	P255/35ZR18	82W	A7 / R7	10.3″	24.8″	77.8″	8.5-10.0″	9.0″	10.8″	X	X
46836	P275/35ZR18	87W	A7 / R7	10.3″	25.5″	80.2″	9.0-11.0″	9.5″	10.7″	X	X
46840	P285/30ZR18	86W	A7 / R7	10.9″	24.9″	78.1″	10.0-11.0″	10.0″	11.5″	X	X
46843	P295/30ZR18	88W	A7 / R7	10.8″	25.3″	79.5″	9.5-11.0″	10.0″	11.6″	X	X
46844	P295/40ZR18	98W	A7 / R7	10.4″	27.2″	85.6″	10.0-11.5″	10.5″	11.9″		X
46846	P315/30ZR18	91W	A7 / R7	11.8″	25.6″	80.5″	11.0-12.0″	11.0″	12.5″	X	X
46847	P315/40ZR18	102W	A7 / R7	11.3″	27.3″	85.7″	10.5-12.5″	11.0″	13.2″		X
46850	P335/30ZR18	95W	A7 / R7	12.8″	25.6″	80.5″	12.0-13.0″	12.0″	13.5″	X	X
46855	P345/35ZR18	100W	A7 / R7	13.2″	26.8″	84.2″	11.0-13.0″	12.0″	13.9″	X	X
46916	P235/35ZR19	79W	A7 / R7	9.25″	25.6″	80.5″	8.0-9.5″	9.0″	10.2″	X	X
46925	P265/35ZR19	86W	A7 / R7	9.6″	26.2″	82.3″	9.0-10.0″	9.0″	10.4″	X	X
46935	P295/30ZR19	89W	A7 / R7	10.4″	26.1″	82.1″	10.0-12.0″	10.0″	11.5″	X	X
46936	P295/35ZR19	92W	A7 / R7	10.0″	27.3″	86.0″	10.0-12.0″	10.0″	11.5″		X
46937	P315/30ZR19	93W	A7 / R7	12.0″	26.1″	82.2″	11.0-12.0″	11.0″	12.5″	X	X
46938	P315/35ZR19	96W	A7 / R7	11.3″	27.3″	85.7″	11.0-12.0″	12.0″	13.2″		X
46940	P315/40ZR19	103W	A7 / R7	11.3″	28.9″	90.7″	11.0-12.0″	11.0″	12.9″		X
46945	P325/30ZR19	94W	A7 / R7	12.2″	26.8″	84.1″	12.0-13.0″	13.0″	13.6″	X	X
46950	P345/30ZR19	98W	A7 / R7	13.0″	26.8″	84.3″	12.0-13.0″	13.0″	14.1″	X	X
46955	P245/35ZR20	95W	A7 / R7	9.1″	26.8″	84.3″	9.0-10.0″	8.5″	9.8″		X
46965	P265/30ZR20	95W	A7 / R7	9.8″	26.7″	83.9″	9.0-10.0″	9.5″	10.9″		X
46975	P285/30ZR20	99W	A7 / R7	9.9″	26.7″	84.0″	9.0-10.0″	10.0″	11.5″		X
46986	P305/30ZR20	103W	A7 / R7	11.8″	27.1″	85.3″	11.0-12.0″	12.0″	13.2″		X
46996	P335/25ZR20	103W	A7 / R7	12.8″	27.1″	85.5″	12.0-13.0″	12.0″	14.2″	X	X

WARNING: *DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for making and performance only and are* ***NOT INTENDED FOR HIGHWAY USE.*** *It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible* ***SERIOUS PERSONAL INJURY OR DEATH.***

SLICK

TDR



VINTAGE

SPEEDSTER

A7 / R7

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.

REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

CIRCUIT RACING D.O.T. - RADIAL WET

ITEM NUMBER	TIRE SIZE	LOAD/SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH
46100	P185/60R13 H20	86H	D.O.T. Radial Wet	6.8″	21.7″	68.1″	5.0-6.0″	6.0″	7.7″
46105	P205/60R13 H20	86H	D.O.T. Radial Wet	7.1″	23.5″	73.8″	6.0-7.5″	6.0″	8.5″
46115	P205/55R14 H20	85H	D.O.T. Radial Wet	7.1″	23.5″	73.8″	6.5-7.5″	6.5″	8.7″
46125	P205/50R15 H20	84H	D.O.T. Radial Wet	7.1″	23.5″	73.8″	6.5-7.5″	6.5″	8.2″
46125	P205/50R15 SMW	84H	D.O.T. Radial Wet	7.1″	23.5″	73.8″	6.5-7.5″	6.5″	8.2″
46127	P225/45R15 H20	81H	D.O.T. Radial Wet	8.9″	22.9″	72.0″	7.0-8.5″	8.0″	9.4″
46135	P205/45R16 H20	77H	D.O.T. Radial Wet	7.1″	23.5″	73.8″	7.0-7.5″	7.0″	8.4″
46140	P225/50R16 H20	91H	D.O.T. Radial Wet	8.8″	24.8″	77.9″	7.0-9.0″	7.0″	9.6″
46145	P245/45R16 H20	88H	D.O.T. Radial Wet	9.0″	24.8″	77.9″	7.0-9.0″	8.0″	10.0″
46150	P255/50R16 H20	99H	D.O.T. Radial Wet	9.3″	26.3″	82.5″	8.0-9.0″	8.0″	10.7″
46170	P225/45R17 H20	84H	D.O.T. Radial Wet	8.8″	24.8″	77.9″	8.0-9.0″	7.5″	9.5″
46175	P245/40R17 H20	86H	D.O.T. Radial Wet	9.0″	24.8″	77.9″	7.0-9.0″	8.0″	10.0″
46185	P275/40R17 H20	93H	D.O.T. Radial Wet	10.0″	25.2″	79.2″	9.0-11.0″	9.5″	11.3″
46200	P225/40R18 H20	83H	D.O.T. Radial Wet	8.8″	24.8″	77.9″	7.0-9.0″	8.0″	9.9″
46205	P245/35R18 H20	80H	D.O.T. Radial Wet	9.0″	24.8″	77.9″	7.0-9.0″	8.0″	10.0″
46207	P245/40R18 H20	88H	D.O.T. Radial Wet	8.75″	25.5″	80.25″	8.0-9.5″	9.0″	9.75″
46215	P275/35R18 H20	87H	D.O.T. Radial Wet	10.0″	25.2″	79.2″	10.0-11.0″	9.5″	11.3″
46220	P305/30R18 H20	89H	D.O.T. Radial Wet	11.8″	25.6″	80.4″	11.0-12.0″	11.0″	12.7″
46230	P325/35R18 H20	130H	D.O.T. Radial Wet	12.0″	27.0″	84.6″	11.0-12.0″	12.0″	13.3″
46260	P325/30R19 H20	130H	D.O.T. Radial Wet	12.0″	27.0″	85.0″	11.0-12.0″	12.0″	13.2″

WARNING: *DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for making and performance only and are* ***NOT INTENDED FOR HIGHWAY USE.*** *It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible* ***SERIOUS PERSONAL INJURY OR DEATH.***

NOTE: H Speed Rating = 130 mph/210 km/h.

FORMULA STUDENT (FSAE)

ITEM NUMBER	TIRE SIZE	APPLICATION	APPROX. WEIGHT	TREAD WIDTH.	APPROX. DIA.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUND SOFT TO FIRM
41100	6.0/18.0-10	FSAE-Slick	8LBS	6.0″	18.1″	6-7″	7.0″	8.5″	LCO
43070	16.0 x 6.0-10	FSAE-Slick	7LBS	6.0″	16.3″	6-7″	6.0″	6.9″	LCO, R25B
43075	16.0 x 7.5-10	FSAE-Slick	8LBS	7.3″	16.2″	6-8″	8.0″	8.4″	LCO, R25B
43101	18.0 x 6.0-10 C2000	FSAE-Slick	9LBS	6.2″	18.1″	6.5-7″	6.0″	8.1″	R25B
43105	18.0 x 7.5-10	FSAE-Slick	10LBS	7.5″	18.3″	7-8″	8.0″	9.5″	R25B
43110	19.5 x 6.5-10	FSAE-Slick	10LBS	6.5″	19.4″	5.5-7″	6.0″	8.2″	R25B
43120	19.5 x 7.5-10	FSAE-Slick	11LBS	7.5″	19.5″	7-8″	8.0″	9.5″	R25B
43163	20.5 x 7.0-13 A2500	FSAE-Slick	11LBS	7.0″	21.0″	5.5-8″	6.0″	8.0″	R25B
43168	20.0 x 7.5-13 A2500	FSAE-Slick	12LBS	8.0″	20.6″	7-9″	8.0″	9.4″	R25B
44070	16.0 x 7.0-10	Circuit Wet - Bias	7.5LBS	7.0″	16.2″	6-7″	6.0″	7.6″	WSet
44115	18.0 x 6.0-10	FSAE-Wet	9LBS	6.2″	17.8″	6-8″	6.0″	7.8″	Wet
44125	19.5 x 6.5-10	Circuit Wet - Bias	10LBS	6.2″	19.5″	6-8″	6.0″	8.2″	Wet
44150	20.0 x 7.5-13	Circuit Wet - Bias	12LBS	7.4″	20.6″	6-8″	7.0″	8.3″	Wet
44185	21.0 x 6.5-13	Circuit Wet - Bias	11LBS	6.7″	21.2″	6-8″	6.0″	7.2″	Wet
43329	205/470R13	FSAE-Radial Slick	8.4LBS	6.9″	18.8″	6-8″	7.0″	7.5″	Continental FSAE Dry
44302	205/470R13	FSAE-Radial Wet	9.3	7.2	18.4	6-7	7.0	7.75	Continental FSAE Wet

RALLY

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	MODEL
44002	165/80R13	Gravel Rally - Right	5.3″	23.5″	74.0″	6.0″	6.0″	7.3″	GTH-R
44003	165/80R13	Gravel Rally - Left	5.3″	23.5″	74.0″	6.0″	6.0″	7.3″	GTH-L
44004	185/70R13	Gravel Rally - Right	5.8″	23.5″	74.0″	7.0″	7.0″	8.2″	GTH-R
44005	185/70R13	Gravel Rally - Left	5.8″	23.5″	74.0″	7.0″	7.0″	8.2″	GTH-L
44006	185/65R15	Gravel Rally Right	6.5″	24.8″	78.0″	6.0″	6.0″	7.4″	GTH R
44007	185/65R15	Gravel Rally - Left	6.5″	24.8″	78.0″	6.0″	6.0″	7.4″	GTH-L
44008	195/65R15	Gravel Rally - Right	6.7″	25.2″	79.0″	7.0″	6.0″	7.7″	GTH-R
44009	195/65R15	Gravel Rally - Left	6.7″	25.2″	79.0″	7.0″	6.0″	7.7″	GTH-L
44010	205/65R15	Gravel Rally - Right	7.1″	25.3″	79.5″	7.0″	7.0″	8.75″	GTH-R
44011	205/65R15	Gravel Rally - Left	7.1″	25.3″	79.5″	7.0″	7.0″	8.75″	GTH-L
44300	200/530R13	Tarmac Rally	7.6″	20.8″	65.5″	7.5″	7.0″	7.6″	WET, DS
44305	200/530R13	Tarmac Rally	7.6″	20.8″	65.5″	7.5″	7.0″	7.6″	DM, DH
44310	220/530R13	Tarmac Rally	7.8″	20.8″	65.5″	7.5″	7.0″	8.3″	WET, DS
44315	220/530R13	Tarmac Rally	7.8″	20.8″	65.5″	7.5″	7.0″	8.3″	DM, DH
44500	200/580R15	Tarmac Rally	7.5″	22.7″	71.5″	7.5″	7.0″	8.6″	WET, DS
44510	200/580R15	Tarmac Rally	7.5″	22.7″	71.5″	7.5″	7.0″	8.6″	DM, DH
44520	185/580R15	Tarmac Rally	6.7″	22.7″	71.5″	7.0″	7.0″	7.9″	WET, DS
44521	185/580R15	Tarmac Rally	6.7″	22.7″	71.5″	7.0″	7.0″	7.9″	DM, DH
44805	200/650R18	Tarmac Rally	8.2″	25.3″	79.5″	8.0″	8.0″	8.9″	WET, DS
44810	200/650R18	Tarmac Rally	8.2″	25.3″	79.5″	8.0″	8.0″	8.9″	DM, DH

CIRCUIT D.O.T. RADIAL WET

FSAE-Slick

CIRCUIT WET BIAS

FSAE WET

CIRCUIT WET

GRAVEL RALLY

TARMAC RALLY

REFER TO INSIDE FRONT COVER FOR NO WARRANTY POLICY AND WARNINGS.

INDEPENDENT DEALERS MUST ESTABLISH THEIR OWN PRICES.
FOR PRICING CONTACT YOUR NEAREST DISTRIBUTOR ON BACK OF CATALOG.